



Overview

The CoreIP UCS-1000 RPS 2U (Industry Standard COTS Server) chassis with 550W RPS delivers a compact and Versatile server at an affordable price. Deploy the portable form factor in small, remote or branch offices, as a compact yet powerful point of sale platform in transport, retail and hospitality environments, or as a flexible configuration for customization in space constrained environments of military and government customers. CoreIP UCS-1000 chassis with 550W RPS blends performance, reliability and manageability. This 2U server powered by uniprocessor board provides unique enterprise-class capabilities at a great value—making it an ideal rack server platform for growing businesses, enterprises, and service providers. Outstanding configuration flexibility caters to a variety of business requirements and a range of CoreIP Qualified Options to fit most needs.



CoreIP UCS-1000 RPS

Key Features

- Redundant Power supply with High power efficiency.
- CoreIP UCS-1000RPS is a short-depth chassis of 15.05 inch providing mobility and easy deployment in a wide variety of environments.
- CoreIP UCS-1000RPS is BIS Certified and has ISO 9001/ISO14001 certification with great quality and design features that are a hallmark of the CoreIP family such as tool-less access to system components and enhanced service ability.

- 1. 550W Redundant Power Supply.**
- 2. VGA port**
- 3. Two NIC Port**
- 4. 4 USB 3.0 Port.**
- 5. Slot 2 PCIe 3.0**
- 6. Power Button**
- 7. Restart Button**
- 8. LEDs of NIC and Hard disk**
- 9. Available in Customized Requirement**

Technical specifications

Model Name	CoreIP UCS - 1000 RPS
Form Factor	2U Rack Mountable with slider
Processor	Intel/AMD *
Processor core	available up-to 64 Cores
Processor cache	45 MB L3*
Processor speed	Up to 4.0 GHz
Memory	64 GB*
Memory slots	4 DIMM slots*
System fan features	hot plug and redundant
Network controller	1GB 361i Ethernet adapter 2 ports (or) 1Gb 332i Ethernet adapter 2ports SATA Controller-Intel C242 Chipset, minimum 1Tb SATA SSD 6Gb/s ports + 2* M.2 Connector*1 For (Linux/Windows)
Storage controller	15 kg minimum 20 kg maximum
Weight of Server	R-93021865
BIS	

Ordering Information:

CoreIP UCS 1000 RPS - 1U chassis with 4 HS bays / 300W RPS / Xeon E-2468 CPU with heat sink / 1 * 32 GB DDR5 ECC U-DIMM / 2 * 512 GB SATA SSD

*Note: Processor, RAM, HDD...etc. model/capacity may be changed to equivalent or higher as per requirement.....



No. C-421, 4th Floor the i-thum, Sector-62, Noida - 201309
(INDIA)



0120-6618000



info@coreip.co.in



www.coreip.co.in