



Overview

The CoreIP UCS-1000 RPS 2U (Industry Standard COTS Server) chassis with 550W RPS delivers a compact and Versatile server at an affordable price. Deploy the portable form factor in small, remote or branch offices, as a compact yet powerful point of sale platform in transport, retail and hospitality environments, or as a flexible configuration for customization in space constrained environments of military and government customers. CoreIP UCS-1000 chassis with 550W RPS blends performance, reliability and manageability. This 2U server powered by uniprocessor board provides unique enterprise-class capabilities at a great value—making it an ideal rack server platform for growing businesses, enterprises, and service providers. Outstanding configuration flexibility caters to a variety of business requirements and a range of CoreIP Qualified Options to fit most needs.



CoreIP UCS-1000 RPS

Key Features

- Redundant Power supply with High power efficiency.
- CoreIP UCS-1000RPS is a short-depth chassis of 15.05 inch providing mobility and easy deployment in a wide variety of environments.
- CoreIP UCS-1000RPS is BIS Certified and has ISO 9001/ISO14001 certification with great quality and design features that are a hallmark of the CoreIP family such as tool-less access to system components and enhanced service ability.

1. 550W Redundant Power Supply.

2. VGA port

3. Two NIC Port

4. 4 USB 3.0 Port.

5. Slot 2 PCIe 3.0

6. Power Button

7. Restart Button

8. LEDs of NIC and Hard disk

9. Available in Customized Requirement

Technical specifications

Model Name	CoreIP UCS – 1000 RPS
Form Factor	2U Rack Mountable with slider
Processor	Intel® Xeon® Processor
Processor core	available 24/16/8/6/4/2
Processor cache	Up to 16 MB L3
Processor speed	Up to 4.0 GHz
Maximum memory	Up to 64 GB
Memory slots	4 DIMM slots
System fan features	hot plug and redundant
Network controller	1GB 361i Ethernet adapter 2 ports (or) 1Gb 332i Ethernet adapter 2ports
Storage controller	SATA Controller-Intel C242 Chipset, minimum 1Tb SATA SSD 6Gb/s ports + 2* M.2 Connector*1 For (Linux/Windows)
Weight of Server	15 kg minimum 20 kg maximum
BIS	R-93021865

Ordering Information:

- 1. Video Management & Recording Server** - CoreIP UCS 1000 RPS - 2U chassis with 8 HS bays / with Redundant Power Supply / 1* 4116 CPU (12 Core) with heat sink / 1*16GB RAM/ RAID card with 1 GB cache / 4 * 600GB SSD with higher capacity / 1 * slim DVD-RW / 1 * Dual port 1G Onboard LAN/ Ethernet
- 2. AI Video Analytics Server**- CoreIP UCS 1000 RPS - 2U chassis with 8 HS bays / with Redundant Power Supply / 1* 4116 CPU (12 Core) with heat sink / 1* 8 GB ECC R-DIMM/ RAID card with 1 GB cache / 4 * 600GB SSD with higher capacity / 1 * slim DVD-RW / 1 * Dual port 1G Onboard LAN/ Ethernet / T1000 8GB graphical card
- 3. FRS Server** - CoreIP UCS 1000 RPS - 2U chassis with 8 HS bays / with Redundant Power Supply / 1* 6130 CPU (16 Core) with heat sink / 1*32 GB RAM/ RAID card with 1 GB cache / 4 * 600GB SSD with higher capacity/ 1 * slim DVD-RW / 1 * Dual port 1G Onboard LAN/ Ethernet / T1000 8GB graphical card

Note: Processor, RAM,HDD...etc. model/capacity may be changed to equivalent or higher.....



No. C-421, 4th floor the i-Thum, Sector-62, Noida - 201309
(INDIA)



0120-6618000



info@coreip.co.in



www.coreip.co.in